





PA - Value Series: Advanced Features, A Affordable Price

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
PA502S	DLP Lamp	SVGA (800x600)	800 x 600	3,500 ANSI lm 22,000:1	4:3	1.97 ~ 2.17	1.1x optical zoom	USB Type A (5V 2A) , Mini USB Type B, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), VGA In, Composite RCA Video In, RGB Input
PA502X	DLP Lamp	XGA (1024x768)	1024 x 768	3,500 ANSI lm 22,000:1	4:3	1.97 ~ 2.17	1.1x optical zoom	USB Type A (5V 2A) , Mini USB Type B, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), VGA In, Composite RCA Video In, RGB Input
PA503S	DLP Lamp	SVGA (800x600)	800 x 600	3,600 ANSI lm 22,000:1	4:3	1.96 ~ 2.15	1.1x optical zoom	Mini USB Type B, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), VGA In(x2), VGA Out, Composite RCA Video In
PA503W	DLP Lamp	WXGA (1280x800)	1280 x 800	3,600 ANSI lm 22,000:1	16:10	1.55- 1.70	1.1x optical zoom	3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDM In, VGA In(x2), VGA Out, Composite RCA Video In, Mini USB
PA503X	DLP Lamp	XGA (1024x768)	1024 x 768	3,600 ANSI lm 22,000:1	4:3	1.96 ~ 2.15	1.1x optical zoom	Mini USB Type B, Audio Output (Mini Jack), 3.5mm Audio In, Control (RS232), VGA In(x2), VGA Out, Composite RCA Video In
PA505W	DLP Lamp	WXGA (1280x800)	1280 x 800	3,500 ANSI lm 22,000:1	16:10	1.5-1.7	1.1x optical zoom	USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDM In(x2), VGA In(x2), VGA Out, Composite RCA Video In, Mini USB

PG - Business/Education Series: Boardroom & Classroom Projection






PX - Home Theater (1080p) Series: True Cinema Experience

Product

Product	Type	Resolution	Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
PX700HD	DLP Lamp	HD (1920x1080)		1920 x 1080	3,500 ANSI lm / 12,000:1	16:9	1.5 - 1.65	1.1x optical zoom	USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI In(x2), VGA In, VGA Out, Mini USB
PX703HD	DLP Lamp	HD (1920x1080)		1920 x 1080	3,500 ANSI lm	16:9	1.13-1.47	-	USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4 (with HDCP 1.4), VGA In, VGA Out
PX706HD	DLP Lamp	HD (1920x1080)		1920 x 1080	3,000 ANSI lm / 22,000:1	16:9	0.69-0.83	1.2x optical zoom	USB 3.1 Type C, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), VGA In, Composite RCA Video In, Mini USB
PX725HD	DLP Lamp	HD (1920x1080)		1920 x 1080	2,000 ANSI lm / 22,000:1	16:9	1.5- 1.65	1.1x Manual optical zoom / manual optical focus	USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS-232), HDMI 1.4 (with HDCP 1.4), VGA In, Composite RCA Video In, Mini USB, RCA Audio In (L/R)
PX727-4K	DLP Lamp	4K (3840x2160)		3840 x 2160	2,200 ANSI lm / 12,000:1	16:9	1.5 - 1.8	1.2x optical zoom	USB 2.0 Type A, 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4 (with HDCP 1.4), HDMI 2.0 (with HDCP 2.2), VGA In, Mini USB
PX727HD	DLP LED	HD (1920x1080)		1920 x 1080	2,000 ANSI lm	16:9	1.13-1.47	-	USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4 (with HDCP 1.4), VGA In, VGA Out
PX747-4K	DLP Lamp	4K (3840x2160)		3840 x 2160	3,500 ANSI lm / 12,000:1	16:9	1.47 - 1.76	1.2x optical zoom	USB 2.0 Type A, 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4 (with HDCP 1.4), HDMI 2.0 (with HDCP 2.2), VGA In, Mini USB
PX800HD	DLP Lamp	HD (1920x1080)		1920 x 1080	2,000 ANSI lm / 100,000:1	16:9	0.23	Manual optical focus	USB Micro B (5V 2A) , Mini USB Type B, Audio Output (Mini Jack), 3.5mm Audio In(x2), Control (RS232), HDMI 1.4/MHL 2.0, Composite RCA Video In, RGB Input(x2)

PS - Ultra Short Throw (Interactive) Series: Big Images Anywhere



Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
PS700X	DLP Lamp	XGA (1024x768)	1024 x 768	3,300 ANSI lm 10,000:1	4:3	0.29	Fixed Zoom	USB 2.0 Type A(x2), Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDM In(x2), HDM 1.4 (with HDCP 1.4), VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB, RCA Audio In (L/R)
PS750HD	DLP Lamp	HD (1920x1080)	1920 x 1080	3,300 ANSI lm 10,000:1	16:9	0.22	Manual optical focus	USB 2.0 Type A(x2), Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, RS232 Out, HDM In, HDM MHL, VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB(x2), RCA Audio In (L/R)
PS750W	DLP Lamp	WXGA (1280x800)	1280 x 800	3,300 ANSI lm 10,000:1	16:10	0.23	Manual optical focus	USB 2.0 Type A, USB Type A (5V 2A) , Mini USB Type B(x2), Audio Output (Mini Jack), Ethernet LAN (RJ45), 3.5mm Audio In, Control (RS232), HDM 1.4/MHL 2.0, VGA Out, Composite RCA Video In, S-Video In, RCA Audio In (L/R), RGB Input(x2)

LS - Laser Series: Long-Lasting Laser Projection

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
LS620X	DLP Laser	XGA (1024x768)	1024 x 768	3,200 ANSI lm 100,000:1	4:3	0.61	Digital optical focus	USB Type A (5V 2A) , Audio Output (Mini Jack), Ethernet LAN (RJ45), 3.5mm Audio In, HDM 1.4/MHL 2.0, VGA Out, RGB Input(x2)
LS625W	DLP Laser	WXGA (1280x800)	1280 x 800	3,200 ANSI lm 100,000:1	16:10	0.52	Fixed Zoom	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDM 1.4 (with HDCP 1.4)(x2), VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB
LS625X	DLP Laser	XGA (1024x768)	1024 x 768	3,200 ANSI lm	4:3	0.49	Fixed Zoom	Ethernet LAN (RJ45), 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDM 1.4 (with HDCP 1.4), VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB
LS700-4K	DLP Laser	4K (3840x2160)	3840 x 2160	3,300 ANSI lm 3,000,000:1	16:9	1.13- 1.47	1.3x Manual optical zoom / manual optical focus	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDM 1.4 (with HDCP 1.4), HDM 2.0 (with HDCP 2.2), VGA In(x2), VGA Out, Composite RCA Video In, Mini USB
LS700HD	DLP Laser	HD (1920x1080)	1920 x 1080	3,500 ANSI lm 3,000,000:1	16:9	1.13- 1.47	1.3x Manual optical zoom / manual optical focus	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDM 1.4 (with HDCP 1.4)(x2), VGA In(x2), VGA Out, Composite RCA Video In, Mini USB
LS750WU	DLP Laser	WUXGA (1920x1200)	1920 x 1200	5,000 ANSI lm 3,000,000:1	16:10	1.13-1.47	1.3x optical zoom	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In, Control (RS-232), HDM 1.4 (with HDCP 1.4)(x2), VGA In, VGA Out, Composite RCA Video In, S-Video In, RCA Audio In (L/R), 3D VESA
LS800HD	DLP Laser	HD (1920x1080)	1920 x 1080	5,000 ANSI lm 100,000:1	16:9	1.2-1.9	1.65x optical zoom	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS-232), HDM In(x3), VGA In, VGA Out, Composite RCA Video In, Mini USB, RCA Audio In (L/R), RCA Audio Out, 3D VESA, HDBT
LS800WU	DLP Laser	WUXGA (1920x1200)	1920 x 1200	5,500 ANSI lm 100,000:1	16:10	1.2 - 1.9	1.65x optical zoom	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDM In(x3), VGA In, VGA Out, Composite RCA Video In, Mini USB, RCA Audio In (L/R), RCA Audio Out, 3D VESA, HDBT

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
LS810	DLP Laser	WXGA (1280x800)	1280 x 800	5,200 ANSI lm 100,000:1	16:10	0.23	Digital optical focus	

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
PRO9510L	DLP Lamp	XGA (1024x768)	1024 x 768	6,200 ANSI lm 8,000:1	4:3	1.3 - 2.21:1	1.7x Manual optical zoom / manual optical focus	USB 2.0 Type A, USB 2.0 Type B, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x3), Control (RS232), HDM MHL, DVI-D, VGA In(x2), VGA Out, Composite RCA Video In, RCA Audio Out, 3D VESA, Wired Remote In, Wired Remote Out, 5-BNC
PRO9520WL	DLP Lamp	WXGA (1280x800)	1280 x 800	5,200 ANSI lm 8,000:1	16:10	1.32 - 2.24:1	1.7x Manual optical zoom / manual optical focus	USB 2.0 Type A, USB 2.0 Type B, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x3), Control (RS232), HDM MHL, DVI-D, VGA In(x2), VGA Out, Composite RCA Video In, RCA Audio Out, 3D VESA, Wired Remote In, Wired Remote Out, 5-BNC
PRO9800WUL	DLP Lamp	WUXGA (1920x1200)	1920 x 1200	5,500 ANSI lm 15,000:1	16:10	1.25 - 2.13:1	1.7x Manual optical zoom / manual optical focus	USB 2.0 Type A, USB 2.0 Type B, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x3), Control (RS232), HDM MHL, DVI-D, VGA In(x2), VGA Out, Composite RCA Video In, RCA Audio Out, 3D VESA, Wired Remote In, Wired Remote Out, 5-BNC

PJD7 - Multimedia Series: Immersive Multimedia

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
PJD7828HDL	DLP Lamp	HD (1920x1080)	1920 x 1080	3,200 ANSI lm	16:9	1.15- 1.5	1.3x Manual optical zoom / manual optical focus	USB 2.0 Type A, USB Micro B (5V 2A) , 3.5mm Audio Out, 3.5mm Audio In, 3.5mm Mc In, HDM MHL, VGA Out, Composite RCA Video In, S-Video In, 15-pin mini D-Sub (x1)

PJD6 - Networkable Series: Facility-wide Control

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
PJD6352	DLP Lamp	XGA (1024x768)	1024 x 768	22,000:1	4:3 (native)	1.51-1.97	1.3x Manual optical zoom / manual optical focus	Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x2), HDM In, HDM MHL, Composite RCA Video In, Mini USB
PJD6552LW	DLP Lamp	WXGA (1280x800)	1280 x 800	3,500 ANSI lm 22,000:1	16:10	1.21 - 1.57	1.3x Manual optical zoom / manual optical focus	Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x2), HDM MHL, VGA In(x2), VGA Out, Composite RCA Video In, Mini USB, 15-pin mini D-Sub (x2)

Mt

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
Mt	DLP LED	WVGA (854x480)	854 x 480	250 lm 120,000:1	16:9	1.2	Fixed Zoom	